






FITTING INSTRUCTIONS FOR ECC0132 RHS CLUTCH COVER
DUCATI 848 STREET-FIGHTER



In this kit there should be:
1 x Engine Case Cover (ECC0132).
2 x M6x90mm CAP HEAD BOLTS
1 x M5x25mm long button head bolt.
1 x M5 Washer.
1 x Spacer (S0554).



PICTURE 'A'



PICTURE 'B'




PLEASE READ THESE INSTRUCTIONS FULLY BEFORE STARTING

- Remove the four bolts arrowed in picture 'A' and remove the lower right-hand side panel.
- Please make sure the engine is cold before proceeding with the fitting of the R&G cover.
- Remove the oil filler cap.
- Remove the two engine case bolts arrowed in the top picture and the smaller bolt arrowed in the top picture from the panel bracket.
- Hold the cover loosely over the case to help identify the correct ones. **DO NOT REMOVE ALL OF THE CASE BOLTS.**
- Offer up the R&G cover to the engine and carefully fit it over the engine casing. Ensure that the three R&G bolts are lined up with the holes in the engine casing, and then push on as far as it will go.
- With a 5mm Allen key tighten the two upper bolts with washers equally so that they pull the cover into place. **DO NOT FULLY TIGHTEN.**
- Place the spacer behind the new engine case cover and use the smaller bolt and washer to secure as shown in picture 'B'.
- Finally use a torque wrench set at 10 Nm (7 Lb ft) to fully tighten the top two bolts.
- Refit the oil filler cap.
- Refit the lower right hand side panel.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.
- NOTE for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent
- **AVOID HARMFUL CHEMICALS IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.**
- R&G will accept no liability if the above procedure and torque settings are not followed.

ISSUE 2 7/11/2022 NEW SPACER UPDATE





Instructions de montage pour ECC0132 Protection embrayage coté droit
DUCATI 848 STREET-FIGHTER



Le kit doit contenir:

- 1 x Protection carter moteur (ECC0132).
- 2 x M6x90mm Boulons
- 1 x M5x25mm Boulon
- 1 x M5 Rondelle.
- 1 x Entretoise (S0554).



Lire les instructions de montage avant de procéder à l'installation



- Enlever les 4 boulons (photo A) et enlever la plaque inférieure du coté droit.
- Vérifier que le moteur soit bien froid avant de commencer.
- Enlever le capuchon d'huile
- Enlever les 2 boulons de carter (photo du haut) et le plus petit boulon (photo du haut) du support de panneau
- Tenir la protection autour du carter pour identifier les bons trous. NE PAS ENLEVER TOUS LES BOULONS DE CARTER.
- Monter la protection en faisant attention à bien à bien la positionner. Assurez-vous que les 3 boulons R&G soient bien alignés avec les trous puis enfoncez au plus profond.
- Avec une clé Allen de 5mm, serrez les 2 boulons les plus haut de façon égale de façon à ce qu'ils mettent la protection en place. NE PAS BLOQUER.
- Placer l'entretoise derrière la nouvelle protection carter moteur et utiliser le boulon le plus petit et la rondelle pour fixer le tout (photo B).
- Utiliser une clé dynamométrique à 10 Nm (7 Lb ft) pour fixer les 2 boulons du haut.
- Remettre le capuchon d'huile.
- Remettre la plaque inférieure coté droit.
- Vérifier les serrages au moins une fois par mois, lors du nettoyage par exemple.
- NOTE: Utiliser uniquement un chiffon doux pour le nettoyage et un agent nettoyant qui ne soit pas trop agressif.
- Utiliser des produits nettoyants trop puissants pourrait altérer l'efficacité de la protection.
- R&G ne sera pas responsable si la procédure indiquée n'est pas respectée, et si les serrages de couple ne sont pas ceux indiqués.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com