



Fitting Instructions for RAD0144BK Radiator Guard
HONDA CBR1100 BLACKBIRD '01-'08



In This Kit There Should Be
1x Radiator Guard (RAD0144BK)
1x 4mm Cable Ties 220mm Long
2x 100mm Lengths of self-adhesive Foam



Picture 1



Picture 2



Picture 3



Picture 4



Picture 5



Picture 6



Picture 7



Picture 8

TOOLS REQUIRED

- Cable cutters
- Socket set to include 8mm socket & wrench.



FITTING INSTRUCTIONS

- To fit the radiator guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.
- Remove both side fairings and the plastic radiator surround from the motorcycle to gain access to the radiator.
- Remove the two bolts that secure the top of the oil cooler in place, as shown in picture 1.
- Remove the bolt that secures the bottom of the oil cooler radiator to the side of the radiator on both sides of the bike, as shown in picture 1. The oil cooler radiator can now be gently pulled clear of the radiator. *We suggest using a cable tie to suspend this in place whilst fitting the R&G radiator guard, to prevent any strain on the oil lines.*
- Remove the bolt that secures the top of the radiator to the frame on the left side of the bike, as shown in picture 3.
- Slide the bottom of the radiator off the mount at the bottom of the radiator, on the right side of the bike, as shown in picture 4.
- Offer the R&G Radiator Guard into position and locate the top bracket on the right side of the bike over the exposed boss of the upper radiator mount, as shown in picture 5.
- Locate the bottom mounting bracket over the exposed boss of the lower radiator mount, and then refit the radiator, as shown in picture 6.
- On the left side of the bike, locate the radiator guard mount in front of the radiator/frame mount and refit the original bolt, before tightening, as shown in picture 7.
- Locate the cable tie through the top right mount and loop round, before tightening, as shown in picture 8.
- Tighten the cable ties and cut off any excess, ensuring the radiator guard is correctly fitted.
- Refit the oil cooler radiator as removed.
- Refit the plastic radiator surround and both side fairings.

ISSUE 1 16/01/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



**Instructions de montage RAD0144BK Grille de protection radiateur HONDA
CBR1100 BLACKBIRD '01-'08**



Le kit doit contenir:

- 1 x Grille de protection radiateur (RAD0144BK)
- 1x 4mm Serre cable 220mm
- 2x 100mm Longueurs de mousse autocollante



Photo 1



Photo 2



Photo 3



Photo 4



Photo 5



Photo 6



Photo 7



Photo 8

Outils requis

- Cutter.
- Clé à molette 8mm



Instructions de montage

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de protection radiateur, de façon à ce que ces bandeaux se situent entre la protection radiateur et le radiateur.
- Enlever le carénage des 2 cotés de la moto pour permettre l'accès au radiateur.
- Enlever les 2 boulons qui fixent le haut du refroidisseur d'huile en place (Photo 1).
- Enlever le boulon qui fixe le radiateur refroidisseur d'huile du côté du radiateur des 2 cotés (Photo 1). Le radiateur refroidisseur d'huile peut maintenant être extrait du radiateur. Nous vous suggérons d'utiliser un serre câble pour le suspendre en place tout en installant la grille de protection radiateur R&G *pour éviter toute gêne sur les conduites d'huile*.
- Enlever le boulon qui fixe le haut du radiateur au cadre du côté gauche de la moto (Photo 3).
- Glisser le bas du radiateur en dehors du support, du côté droit de la moto (Photo 4).
- Mettre la grille de protection radiateur R&G en position et placer le support du haut du côté droit de la moto, autour du patron dépassant du support supérieur de radiateur (Photo 5).
- Loger le bas du support autour du patron dépassant du support radiateur inférieur, puis remettre le radiateur (Photo 6).
- Du côté gauche de la moto, loger le support de protection radiateur devant le radiateur/support de cadre et remettre le boulon d'origine, avant de serrer (Photo 7).
- Placer le serre câble à travers le support en haut à droite et faire une boucle, avant de serrer (Photo 8).
- Serrer les attaches câble et couper ce qui dépasse, en vous assurant que la protection radiateur soit correctement installée.
- Remettre le radiateur refroidisseur d'huile de la même façon qu'il a été enlevé.
- Remettre le contour de radiateur en plastique et le carénage des 2 cotés.

ISSUE 1 16/01/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Montageanleitung für den RAD0144BK Kühlerschutz
HONDA CBR1100 BLACKBIRD '01-'08



Dieser Kit beinhaltet:
1x Kühlerschutz (RAD0144BK)
1x 4mm Kabelbinder 220mm Länge
2x 100mm selbstklebende Schaumstoffstreifen



Abbildung 1



Abbildung 2



Abbildung 3



Abbildung 4



Abbildung 5



Abbildung 6



Abbildung 7



Abbildung 8

SIE BENÖTIGEN FOLGENDES WERKZEUG:

- Seitenschneider
- 8mm Steckschlüssel



MONTAGEANLEITUNG

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoffstreifen in 10 mm breiten Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind.
- Entfernen Sie beide Seitenverkleidungen und die Plastikverkleidung für den Kühler, um Zugang zum Kühler zu ermöglichen.
- Entfernen Sie die zwei Schrauben, die den Ölkühler oben befestigen (siehe Abbildung 1).
- Entfernen Sie die Schraube, die den Ölkühler an der Seite des Kühlers befestigt (auf beiden Seiten des Motorrads entfernen), wie in Abbildung 1 abgebildet. Der Ölkühler kann nun vorsichtig vom Kühler entfernt werden. *Wir empfehlen, den Ölkühler während der Montage des Kühlerschutzes mit einem Kabelbinder anzuhängen, um unnötige Belastung auf den Ölleitungen zu vermeiden.*
- Entfernen Sie die Schraube, die den Kühler oben am Rahmen auf der linken Seite des Motorrads befestigt – siehe Abbildung 3.
- Schieben Sie den Kühler vorsichtig von der Halterung unten am Kühler (auf der rechten Seite des Motorrads) wie in Abbildung 4 abgebildet.
- Halten Sie den R&G Kühlerschutz in Position und fixieren Sie die obere Halterung auf der rechten Seite des Motorrads über der hervorstehenden Lochplatte an der oberen Kühlerhalterung – siehe Abbildung 5.
- Die untere Montagehalterung über der hervorstehenden Lochplatte des unteren Kühlerhalters fixieren, dann den Kühler montieren – siehe Abbildung 6.
- Auf der linken Seite des Motorrads, die Kühlerschutzhalterung vor dem Kühler/Rahmen-Halter anbringen und mit der Originalschraube befestigen – siehe Abbildung 7.
- Einen Kabelbinder in die obere Halterung einführen und um die Halterung wickeln, bevor Sie den festziehen – siehe Abbildung 8.
- Ziehen Sie die Kabelbinder fest und schneiden Sie das überstehende Kabel ab. Überprüfen Sie, dass der Kühlerschutz ordnungsgemäß montiert ist.
- Montieren Sie den Ölkühler wieder wie ursprünglich.
- Montieren Sie die Verkleidung um den Kühler und beide Seitenverkleidungen.

AUSGABE 1 16/01/2013 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com