

Fitting Instructions for OCG0008BK Oil Cooler Guard Oil Cooler Guard - BMW R1200GS 2010-



In This Kit There Should Be 1x Radiator Guard 2x Cable/Zip Ties 2x 100mm Lengths of Foam

- Remove the two bolts and nuts in position arrowed in above picture.
- Remove plastic cowl shown above the oil cooler guard.
- To fit the oil cooler guard to the bike cut the foam strips provided into 10mm wide pieces and stick them to the back of the oil cooler guard, so that they sit between the oil cooler guard and the oil cooler itself.
- Fit the oil cooler guard between mounting brackets of plastic cowl and reposition as original.
- Refit bolts and nuts as original.
- The two cable ties go through the slots at the bottom of the oil cooler guard and through the radiator surround to secure in position.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



FRANCE Instructions de montage de la protection de radiateur d'huile. OCG0008BK - BMW R1200GS 2010-



I <u>Ce kit comprend:</u> 1x protection . 2 x bandes de mousse adhésive 100mm. 2x colliers de serrage.

- Enlever les deux boulons de fixation montrés sur la photo ci-dessus.
- Enlever le cache en plastique situé au dessus du radiateur d'huile.
- Pour fixer la protection de radiateur sur la moto, vous devrez couper et coller des morceaux de 10 mm de mousse au dos de la protection. Ces morceaux de mousse se positionneront entre la protection et le radiateur.
- Placer la protection de radiateur sur la moto, celle-ci sera positionnée entre les pattes de fixation en plastique et le cache en plastique précédemment retiré.
- Utilisez les vis d'origine pour fixer la protection.
- Fixer ensuite les parties basses de la protection à l'aide des colliers de serrage livrés dans le kit. Les câbles de serrage passeront par les trous situés en bas de la protection et à travers le radiateur. Ces fixations permettront de sécuriser l'ensemble sur la moto.

