



FITTING INSTRUCTIONS FOR CP0093BL/WH CRASH PROTECTORS YAMAHA R6 '03-'05 UPPERS

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

TOP FAIRING NEARSIDE (LEFT SIDE AS YOU SIT ON THE BIKE)

- Remove existing engine bolt (located middle of the top fairing - can be seen without removing the fairing)
- Take M10 x 100mm long bolt and slide washer over it
- Assemble bolt through crash protector (the one with the shorter neck)
- Take the thicker spacer and slide it over the bolt and up behind the protector
- Offer the whole assembly up to the bike
- Tighten bolt until you feel some compression from inside the protector. Turn a little more so that you feel the compression increase slightly. Then apply a quarter turn. Do not overtighten as damage can occur to the bike. Do not exceed 40nm of torque.

TOP FAIRING OFFSIDE

- Remove fairing panel
- Unscrew offside engine bolt (the front bolt, directly opposite the exposed engine bolt that you have just replaced on the left side) enough to enable contact with inside of fairing to establish a mark so that the hole is drilled in correct place (suggest marking head of engine bolt with paint).
- Offer fairing panel back up and secure in correct position to establish mark.
- Remove fairing panel
- Drill pilot hole in fairing where marked with paint; check correct alignment
- Using 1 inch (28mm) tank cutter/cone cutter, use pilot hole and drill slowly
- Replace fairing
- Take the M10 x 90mm long bolt and slide the washer over it
- Pass the bolt through the crash protector (the one with the longer neck)
- Slide the spacer over the bolt and up behind the bobbin
- Offer the assembly up to the bike
- Tighten bolt until you feel some compression from inside the protector. Turn a little more so that you feel the compression increase slightly. Then apply a quarter turn. Do not overtighten as damage can occur to the bike. Do not exceed 40nm of torque.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected) Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 2206380 Fax: 01420 521101 www.rg-racing.com Email: info@rg-racing.com